

Make AVM your single source for **Flooring Solutions!**



Take a quiet moment to recharge. Respite creates warmth and a calming space to unwind. The innovative COREtec® XRC technology provides a dimensionally stable construction while the high-density



ShawContract®

product specifications

Style info: Respite, 4090V Wear layer: 20 mil (0.5 mm) | 0.020 in Overall thickness: 0.197 in | 5.0 mm Actual dimensions: 7.20 in x 48.03 in | 18.29 cm x 122.00 cm Finish: ExoGuard™ Installation: floating or direct glue Warranty: 15 year commercial warranty



I ExoGuard[™] Finish Provides superior durability against scratching and abrasion in demanding environments 2 Clear 20 mil Wear Layer Protects against premature product aging **3** High-Resolution Image Creates a stunning visual with depth and detail, the film is laminated directly to the XRC core A Extruded Core Waterproof and dimensionally stable, this core protects the top layers from indentation 5 Attached Cork Underlayment Provides added sound dampening from floor to-floor sound transfer **6** Integrated Locking Edge Eliminates the need for wet adhesive by limiting floor prep and eliminating telegraphing

Respite's innovative Coretec XRC technology delivers high performance and durability in heavy commercial environments. The patented construction is dimensionally stable, waterproof, and scratch resistant. Respite's attached cork underlayment reduces sound transmission, delivering a human centered solution for public and private spaces.

